

Part No: 1806COFRH-C07
Description: 6 x 18(7)AWG Six core Foil Screened Low Smoke Halogen Free (LSHF) Data Cable



Construction

Conductor Material	: Bare Copper, 18(7)awg
Pair Insulation Material	: Cross Linked Polyethylene (XLPE)
Number of Cores	: 6
Overall Screen	: Overall Aluminium Foil (100% Coverage)
Drain Wire	: Tinned Copper, 24awg
Sheath Material	: Low Smoke Halogen Free (LSHF)
Sheath Colour	: Blue
Core Identification	: Black, Red, White, Green, Brown, Blue
Alternative to Belden	: 5304FE

Electrical Characteristics

Nominal Conductor Resistance @20°C	: < 23.8 Ω/km
Nominak Mutual Capacitance	: max pF/m 75
Voltage Rating	: 300v
Test Voltage	: 2000v

Physical Characteristics

Overall Diameter	: 5.7 ± 0.2mm
Min. Bend Radius	: 8 x OD
Temperature Rating	: -30°C to +75°C
Weight	: 75 kg/km

Standards

Flame Retardant	: BS EN 60332-1-2
Low Smoke Generation	: BS EN 61034-2
Halogen Gas Emission	: BS EN 60754-1
RoHS Compliant	: Yes
CE Compliant	: LVD (2014/35/EU), CPR (305/2011)
CPR Classification	: Cca s1a, d2, a1