1822CCCH-E00
Technical Datasheet

Part No: 1822CCCH-E00
Description: 1 Pair 22awg Foil Screened + 2core 18awg Low Smoke Halogen Free (LSHF).

truLIGHTING

CONSTRUCTION PRODUCTS REGULATION
BS EN 50575
CLASS Eca
INDEPENDENTLY VERIFIED

Units

Data

Conductor Material	: Bare Copper, 22(7)awg
Insulation Material	: Foamed Polyethylene (FPE)
Number of Pairs	: 1
Drain Wire	: Tinned Copper, 24(7)awg
Overall Screen	: Overall Aluminium Foil (>100% Coverage)
Pair Identification	: White, Blue

Power

Conductor Material	: Bare Copper, 18(16)awg
Core Insulation	: Low Smoke Halogen Free (LSHF)
Number of Cores	: 2
Core Identification	: Red, Black

Overall Construction

Sheath Material	: Low Smoke Halogen Free (LSHF)
Sheath Colour	: Teal with Yellow Stripe
Alternative to Crestron	: Crestron-NP

Electrical Characteristics

Nom. Conductor Resistance @ 20°C		Data	: ≤ 54.2 Ω/km
		Power	: ≤ 23.7 Ω/km
Insulation Resistance @ 20°c			: ≥ 100 MΩ.M
Capacitance	Core to core	Data	: 41 pF/m ± 20
	Core to screen	Data	: 79 pF/m ± 35
Impedance		Data	: 100 Ω ± 10
Voltage Rating			: 450/750V *Applies to CE marked FSC branded stock only*
Test Voltage			: 2.5kV for 5 minutes

Physical Characteristics

Overall Diameter	: 6.4 ± 0.2mm
Min Bend Radius	: 15 x OD
Temperature Rating	: -20°C to +70°C
Weight	: 46 kg/km

Standards

Flame Retardant	: BS EN 60332-1-2
Low Smoke Generation	: BS EN 61034-2
Halogen Gas Emission	: BS EN 60754-1&2
RoHS3 Compliant	: Yes
CE Compliant	: LVD (2006/95/EC), CPR (305/2011)
CPR Classification	: Eca (EN50575:2014+A1:2016)

FS Cables
Shoal Export
01727 840 841
+44 1727 849 841
sales@fscables.com
sales@shoal-export.com
www.fscables.com
www.shoal-export.com

Information and images on this techincal datasheet are intended for guidance only and products may vary due to manufacturing changes, technical improvements and commercial factors. We reserve the right to amend the product information without notice or liability.