


Part No: 2201POFPL-E00
Description: 1 x 2 x 22(7)AWG Single Pair Foil Screened LSF Data Cable.



Construction

Conductor Material : Tinned Copper, 22(7)awg
 Pair Insulation Material : Polyethylene (PE)
 Number of Pairs : 1
 Overall Screen : Aluminium Foil (100% Coverage)
 Drain Wire : Tinned Copper, 22(7)awg
 Sheath Material : Low Smoke and Fume (LSF)
 Sheath Colour : Grey
 Core Identification : Clear/Black
 Alternative to Belden : 8761

Electrical Characteristics

Nominal Conductor Resistance @20°C : < 55.2 Ω/km
 Capacitance Core to core : 65 pF/m ± 25
 Core to screen : 122 pF/m ± 35
 Impedance : 85 Ω ± 25
 Voltage Rating : 450/750 V *Applies to CE marked FSC branded stock only*
 Test Voltage : 2.5 kV for 5 minutes

Physical Characteristics

Overall Diameter : 4.5 ± 0.2mm
 Min. Bend Radius : 10 x OD
 Temperature Rating : -20°C to +70°C
 Weight : 25 kg/km

Standards

Flame Retardant : BS EN 60332-1-2
 RoHS3 Compliant : Yes
 CE Compliant : LVD (2014/35/EU), CPR (305/2011)
 CPR Classification : Eca (EN50575:2014+A1:2016)