

**Part No:** 2201PUYH-E00  
**Description:** 1 x 2 x 22(7)AWG Unscreened Paired Low Smoke Halogen Free (LSHF) Data Cable



### Construction

Conductor Material : Tinned Copper, 22(7)awg  
 Pair Insulation Material : Low Smoke Halogen Free (LSHF)  
 Number of Pairs : 1  
 Sheath Material : Low Smoke Halogen Free (LSHF)  
 Sheath Colour : Grey  
 Core Identification : Black & Red  
 Alternative to Belden : 8442

### Electrical Characteristics

Nominal Conductor Resistance @ 20°C : < 54.2 Ω/km  
 Capacitance Core to core : 98.4 pF/m ± 10  
 Voltage Rating : 450/750V Applies to CE marked FSC branded stock only  
 Test Voltage : 2.5kV for 5 minutes

### Physical Characteristics

Overall Diameter : 4.3 ± 0.2mm  
 Min. Bend Radius : 10 x OD  
 Temperature Rating : -20°C to +70°C  
 Weight : 23 kg/km

### Standards

Flame Retardant : BS EN 60332-1-2  
 Low Smoke Generation : BS EN 61034-2  
 Halogen Gas Emission : BS EN 60754-1&2  
 RoHS Compliant : Yes  
 CE Compliant : LVD (2014/35/EU), CPR (305/2011)  
 CPR Classification : Eca (EN50575:2014+A1:2016)  
 UV and Weather Resistant : ISO 4892-3\*  
 :\*Applies to all Batches ST\*\*\*\*\* Onwards

