

Part Number: 2202PIFRH-C07
Description: 2 x 2 x 22(7)AWG Two Pair Individually Foil Screened Low Smoke Halogen Free (LSHF) Data Cable



Construction

Conductor Material	: Tinned Copper, 22(7)awg
Insulation Material	: Cross Linked Polyethylene (XLPE)
Number of Pairs	: 2
Individual Screen	: Aluminium Foil, Each Pair (100% Coverage)
Common Drain Wire	: Tinned Copper, 24(7)awg
Outer Sheath Material	: Low Smoke Halogen Free (LSHF)
Outer Sheath Colour	: Grey
Core Identification	: Black/Red, Green/White
Alternative to Belden	: 8723

Electrical Characteristics

Nominal Conductor Resistance	: < 57.4 Ω/km
Insulation Resistance	: > 200MΩ.M
Nominal Mutual Capacitance	: max pF/m 150
Voltage Rating	: 300v
Test Voltage	: 2000v

Physical Characteristics

Overall Diameter	: 6.0 ± 0.2mm
Min. Bend Radius	: 8 x OD
Temperature Rating	: -30°C to +75°C
Weight	: 53 kg/km

Standards

Flame Retardant	: BS EN 60332-1-2
Low Smoke Generation	: BS EN 61034-2
Halogen Gas Emission	: BS EN 60754-1
RoHS Compliant	: Yes
CE Compliant	: LVD (2014/35/EU), CPR (305/2011)
CPR Classification	: Cca s1a, d2, a1