

Part No: 2202PIFRH
Description: 2 x 2 x 22(7)AWG Individual Foil Screened Paired LSHF Data Cable Grey. Low Smoke Halogen Free Throughout.



Construction

Conductor Material	: Tinned Copper, 22(7)awg
Pair Insulation Material	: Polypropylene (PP)
Number of Pairs	: 2
Individual Screen	: Aluminium Foil (100% Coverage)
Common Drain Wire	: Tinned Copper, 24(7)awg
Sheath Material	: Low Smoke Halogen Free (LSHF)
Sheath Colour	: Grey
Core Identification	: Black/Red, Green/White
Alternative to Belden	: 8723

Electrical Characteristics

Nominal Conductor Resistance @20°C	: < 55.2 Ω/km
Insulation Resistance	: > 200MΩ.M
Capacitance	Core to core : 108 pF/m
	Core to screen : 203 pF/m
Voltage Rating	: 450/750V <i>Applies to CE marked FSC branded stock only</i>
Test Voltage	: 2.5kV for 5 minutes

Physical Characteristics

Overall Diameter	: 4.2 ± 0.2mm
Min. Bend Radius	: 10 x OD
Temperature Rating	: -20°C to +70°C
Weight	: 32 kg/km

Standards

Flame Retardant	: EN 60332-1-2
Low Smoke Generation	: EN 61034-2
Halogen Gas Emission	: EN 60754-1&2
RoHS2 Compliant	: Yes
CE Compliant	: LVD (2014/35/EU)