

Part No: 390L60H75-E00
Description: ANT-600 75 Ohm Antennax Low Smoke Halogen Free (LSHF) Black Coaxial Cable



Construction

Conductor Material : Copper Clad Aluminium
 Conductor Size : 1/2.74 mm
 Dielectric : Foam Polyethylene (FPE)
 Diameter of Dielectric : 11.56 mm
 1st Screen Material : Bonded Aluminium Foil
 2nd Screen Material : Tinned Copper Wire Braid (>90% Coverage)
 Outer Sheath Material : Low Smoke Halogen Free (LSHF)
 Outer Sheath Colour : Black

Electrical Characteristics

Impedance : 75 Ω ± 2
 Capacitance @ 1 kHz : 51.2 pF/m ± 5
 Velocity of Propagation : 87 %
 Conductor Resistance @ 20°C : ≤ 4.7 Ω /km
 Screen Resistance @ 20°C : ≤ 5.75 Ω /km
 Peak Power : 40.0 kW

Attenuation @ 20°C

Frequency (MHz)	Attenuation (dB/100ft)	Attenuation (dB/100m)	Frequency (MHz)	Attenuation (dB/100ft)	Attenuation (dB/100m)
30	0.4	1.3	1500	3.1	10.2
50	0.5	1.7	1800	3.5	11.4
150	0.9	3.0	2000	3.7	12.1
220	1.1	3.6	2500	4.2	13.7
450	1.6	5.3	5800	6.9	22.6
900	2.3	7.7			

Return Loss @ 20°C

Frequency (MHz)	Return Loss (dB)
30-2500MHz	≥ 15

Physical Characteristics

Overall Diameter : 15.0 mm (±0.30mm)
 Bending Radius : 5 x OD
 Temperature Rating : -40°C to +75°C
 Weight : 201 kg/km

Standards

Flame Retardant : BS EN 60332-1-2, BS EN 60332-3-24 Cat C
 Low Smoke Generation : BS EN 61034-2
 Halogen Gas Emission : BS EN 60754-1&2
 RoHS Compliant : Yes
 UV & Weather Resistant : ISO 4892-2&3
 CE Compliant : CPR (305/2011)
 CPR Classification : Eca (EN50575:2014+A1:2016)