

## **LSF BURGLAR ALARM CABLE**



PART REFERENCE	39800204W	L
CONSTRUCTION		
CONDUCTOR	TINNED COPPE	R
CONDUCTOR SIZE	0.22MM <sup>2</sup>	
INSULATION	LSF/PVC	
JACKET	LSF/PVC WHITE	
TECHNICAL		
WORKING VOLTAGE	50V	
MAXIMUM CURRENT	1 <b>A</b>	
CONDUCTOR RESISTANCE	< 94.2 Ω/KM	
INSULATION RESISTANCE	> <b>200</b> MΩ.M	
TEMPERATURE RATING	-0 to +70°C (S	TATIC)
COLOUR CODE	4 CORE:	RED, BLUE, YELLOW & BLACK
	6 CORE:	RED, BLUE, YELLOW, BLACK, WHITE & GREEN
	8 CORE:	RED, BLUE, YELLOW, BLACK, WHITE, GREEN, ORANGE & BROWN
	12 CORE:	RED, BLUE, YELLOW, BLACK, WHITE, GREEN, ORANGE, BROWN, GREY, PINK, VIOLET & TURQUOISE
NO COBE WEIGHT	OVERALL DIAMETER	

N <u>o</u> core	WEIGHT KG/KM	DIAMETER (MM)
4	18	3.4
6	25	4.0
8	30	4.3
8	30	4.3
12	37	5.5

Tru is a brand from FSC. Registered office Alban Point Alban Park, Hatfield Road, St Albans AL4 0JX UK







ISO 14001 =

The above product may vary due to manufacturing changes, technical improvements and commercial factors. Overall diameters and weights are given for guidance only and if critical should be confirmed at time of order. All trademarks and tradenames are acknowledged