

## LSF BURGLAR ALARM CABLE





PART REFERENCE 39800208WL

CONSTRUCTION

CONDUCTOR TINNED COPPER

CONDUCTOR SIZE 0.22MM<sup>2</sup>
INSULATION LSF/PVC

JACKET LSF/PVC WHITE

**TECHNICAL** 

WORKING VOLTAGE 50V MAXIMUM CURRENT 1A

CONDUCTOR RESISTANCE  $< 94.2 \ \Omega/KM$  INSULATION RESISTANCE  $> 200 \ M\Omega.M$ 

TEMPERATURE RATING -0 to +70°C (STATIC)

COLOUR CODE 4 CORE: RED, BLUE, YELLOW & BLACK

6 CORE: RED, BLUE, YELLOW, BLACK, WHITE & GREEN

8 CORE: RED, BLUE, YELLOW, BLACK, WHITE, GREEN, ORANGE &

**BROWN** 

12 CORE: RED, BLUE, YELLOW, BLACK, WHITE, GREEN, ORANGE,

**BROWN, GREY, PINK, VIOLET & TURQUOISE** 

N <u>o</u> Core	NOMINAL WEIGHT KG/KM	OVERALL DIAMETER (MM)
4	18	3.4
6	25	4.0
8	30	4.3
8	30	4.3
12	37	5.5







