

LSF SCREENED BURGLAR ALARM CABLE



truSECURITY

PART REFERENCE 39900206WL

CONSTRUCTION

CONDUCTOR TINNED COPPER
CONDUCTOR SIZE 0.22MM²
INSULATION LSF/PVC
SCREEN POLYESTER/ALUMINIUM FOIL
JACKET LSF/PVC WHITE

TECHNICAL

WORKING VOLTAGE 50V
MAXIMUM CURRENT 1A
CONDUCTOR RESISTANCE < 94.2 Ω/KM
INSULATION RESISTANCE > 200 MΩ.M
TEMPERATURE RATING -0 to +70°C (STATIC)

COLOUR CODE

4 CORE: RED, BLUE, YELLOW & BLACK
 6 CORE: RED, BLUE, YELLOW, BLACK, WHITE & GREEN
 8 CORE: RED, BLUE, YELLOW, BLACK, WHITE, GREEN, ORANGE & BROWN
 12 CORE: RED, BLUE, YELLOW, BLACK, WHITE, GREEN, ORANGE, BROWN, GREY, PINK, VIOLET & TURQUOISE

NO CORE	NOMINAL WEIGHT KG/KM	OVERALL DIAMETER (MM)
4	24	3.7
6	28	4.3
8	34	4.6
12	47	6.2