

LSHF SCREENED BURGLAR ALARM CABLE



truSECURITY

PART REFERENCE

3990208WH

CONSTRUCTION

CONDUCTOR	TINNED COPPER
CONDUCTOR SIZE	0.22MM ²
INSULATION	LSHF
SCREEN	POLYESTER/ALUMINIUM FOIL
JACKET	LSHF WHITE

TECHNICAL

WORKING VOLTAGE	50V
MAXIMUM CURRENT	1A
CONDUCTOR RESISTANCE	< 94.2 Ω/KM
INSULATION RESISTANCE	> 200 MΩ.M
TEMPERATURE RATING	-0 to +70°C (STATIC)

COLOUR CODE

4 CORE:	RED, BLUE, YELLOW & BLACK
6 CORE:	RED, BLUE, YELLOW, BLACK, WHITE & GREEN
8 CORE:	RED, BLUE, YELLOW, BLACK, WHITE, GREEN, ORANGE & BROWN
12 CORE:	RED, BLUE, YELLOW, BLACK, WHITE, GREEN, ORANGE, BROWN, GREY, PINK, VIOLET & TURQUOISE

NO CORE	NOMINAL WEIGHT KG/KM	OVERALL DIAMETER (MM)
4	24	3.7
6	28	4.3
8	34	4.6
12	47	6.2