BS 5467 Amoured PVC Power Cable
Technical Datasheet

Description: Multicore low voltage power and control cable that features cross linked insulation, heavy galvanised steel wire armour and black UV stable water resistant PVC jacket. Suitable for internal/external application and in direct burial



CONSTRUCTION PRODUCTS REGULATION
BS EN 50575
CLASS Eca
INDEPENDENTLY VERIFIED

Construction

Conductor Material	: Bare Copper, Class 2
Insulation Material	: Cross Linked Polyethylene (XLPE)
Bedding Material	: Polyvinylchloride (PVC)
Armour	: Galvanised Steel Wire Armour (SWA)
Sheath Material	: Polyvinylchloride (PVC)
Sheath Colour	: Black
Core Identification	: 2core – Brown, Blue 3core – Brown, Black, Grey
	: 4core – Brown, Blue, Black, Grey
	: 5core & Above – White Cores with Black Numbers

Electrical Characteristics

Conductor Resistance	: BS EN 60228
Working Voltage	: 0.6/1kV

Physical Characteristics

Overall Diameter	: See Table
Min. Bend Radius	: 6 x OD
Temperature Rating	: -15°C to +90°C

Standards

Manufactured to	: BS 5467
RoHS3 Compliant	: Yes
Flame Retardant	: BS EN 60332-1-2
CE Compliant	: LVD (2014/35/EU), CPR (305/2011)
CPR Classification	: Eca (EN50575:2014+A1:2016)

Part No.	Cores x mm²	O/D mm	Weight kg/km
54600102-E00	2 x 1.5	11.5	320
54600103-E00	3 x 1.5	12.0	300
54600104-E00	4 x 1.5	12.9	400
54600105-E00	5 x 1.5	14.9	400
54600107-E00	7 x 1.5	15.8	500
54600112-E00	12 x 1.5	20.0	820
54600119-E00	19 x 1.5	22.6	1080
54600127-E00	27 x 1.5	27.3	1850
54600137-E00	37 x 1.5	29.9	1850
54600148-E00	48 x 1.5	33.5	2900
54600202-E00	2 x 2.5	12.9	365
54600203-E00	3 x 2.5	13.0	350
54600204-E00	4 x 2.5	14.4	470
54600205-E00	5 x 2.5	16.5	490
54600207-E00	7 x 2.5	17.6	730
54600212-E00	12 x 2.5	20.1	840
54600219-E00	19 x 2.5	27.0	1530
54600227-E00	27 x 2.5	31.3	1960
54600237-E00	37 x 2.5	34.3	2440
54600402-E00	2 x 4	14.4	440

Part No.	Cores x mm²	O/D mm	Weight Kg/km
54600403-E00	3 x 4	15.0	450
54600404-E00	4 x 4	15.7	580
54600405-E00	5 x 4	18.9	715
54600407-E00	7 x 4	20.1	840
54600412-E00	12 x 4	26.1	1390
54600419-E00	19 x 4	29.7	1850
54600427-E00	27 x 4	34.8	2420
54600437-E00	37 x 4	39.6	3320
54600602-E00	2 x 6	15.6	470
54600603-E00	3 x 6	16.0	550
54600604-E00	4 x 6	17.9	810
54600605-E00	5 x 6	20.4	900
54601002-E00	2 x 10	16.8	810
54601003-E00	3 x 10	18.0	800
54601004-E00	4 x 10	19.7	1080
54601005-E00	5 x 10	23.2	1200
54601602-E00	2 x 16	19.6	1025
54601603-E00	3 x 16	21.0	1100
54601604-E00	4 x 16	22.4	1450
54601605-E00	5 x 16	27.3	1650

Part No.	Cores x mm²	O/D mm	Weight Kg/km
54602502-E00	2 x 25	20.9	1000
54602503-E00	3 x 25	26.0	1700
54602504-E00	4 x 25	27.3	2060
54602505-E00	5 x 25	30.0	2200
54603502-E00	2 x 35	23.0	1400
54603503-E00	3 x 35	28.0	2100
54603504-E00	4 x 35	30.2	2550
54603505-E00	5 x 35	32.9	2700
54605002-E00	2 x 50	25.3	1750
54605003-E00	3 x 50	30.0	2400
54605004-E00	4 x 50	32.2	2875
54605005-E00	5 x 50	37.5	3700
54607002-E00	2 x 70	28.5	2300
54607003-E00	3 x 70	34.0	3100
54607004-E00	4 x 70	38.0	4250
54607005-E00	5 x 70	42.3	5050
54609502-E00	2 x 95	32.3	3100
54609503-E00	3 x 95	36.0	4100
54609504-E00	4 x 95	41.7	5475
54609505-E00	5 x 95	51.0	7500

FS Cables
Shoal Export

01727 840 841
+44 1727 849 841

sales@fscables.com
sales@shoal-export.com

www.fscables.com
www.shoal-export.com

Date: 16/10/2019
Revision: 1.0
Author: SK
Checked: SK

Information and images on this techincal datasheet are intended for guidance only and products may vary due to manufacturing changes, technical improvements and commercial factors. We reserve the right to amend the product information without notice or liability.