

**Description:** Burglar Alarm Cable Unscreened in Low Smoke & Fume (LSF) manufactured in accordance to BS 4737 Type 2.



### Construction

Conductor Material : Tinned Copper, 7/0.2mm  
 Conductor Insulation : Low Smoke & Fume (LSF)  
 Outer Sheath Material : Low Smoke & Fume (LSF)  
 Outer Sheath Colour : White  
 Core Identification :

1	Red	7	Orange
2	Blue	8	Brown
3	Yellow	9	Grey
4	Black	10	Pink
5	White	11	Violet
6	Green	12	Turquoise

### Electrical Characteristics

Nominal Conductor Resistance @ 20°C : < 100 Ω/km  
 Insulation Resistance : > 1 MΩ.KM  
 Voltage Rating : 30 V  
 Test Voltage : 2 kV for 5 Minutes

### Physical Characteristics

Overall Diameter : See Table  
 Min. Bend Radius : 15 x OD  
 Temperature Rating : -0°C to 70°C  
 Weight : See Table

### Standards

Flame Retardant : BS EN 60332-1-2  
 RoHS3 Compliant : Yes  
 Manufactured in accordance to : BS 4737 Type 2  
 CE Compliant : LVD (2014/35/EU), CPR (305/2011)  
 CPR Classification : Eca (EN50575:2014+A1:2016)

Part No.	No. of Cores	Weight kg/km	O/D mm
39800204WL-E00	4	18	3.4
39800206WL-E00	6	25	4.0
39800208WL-E00	8	30	4.3
39800212WL-E00	12	37	5.5