


Part No: C5EFD
Description: The TruLAN Cat 5E cable is the ideal choice for high speed data networks across a home or building. Suitable for Ducts and Outdoors.



**TESTED TO
350MHz**



Construction

Conductor	Bare Copper
AWG	24(1)
Insulation Material	High Density Polyethylene (HDPE)
Number of Pairs	4
Pair Identification	TIA 568
Overall Screen	Aluminium/Polyester
Drain Wire	24(1)AWG, Tinned Copper
Inner Sheath Material	Polyvinyl Chloride (PVC), Grey
Outer Sheath Material	Low Density Polyethylene (LDPE), Black

Electrical Characteristics

Max. Conductor Resistance @ 20°C	≤ 9.5 Ω/100m
Max. Resistance Unbalanced	≤ 2.5 %
Nominal Impedance (1-100MHz)	100 ± 15 Ω
Insulation Resistance	5000MΩ/km
Mutual Capacitance	≤ 5.6nF/100m
Capacitance Unbalanced to Earth	≤ 300 pF/ 100m
NVP	68 %
Max. Delay Skew	≤ 45 nS/ 100m
Voltage Rating EN 50525-1	450/750V*
Test Voltage	2.5kV (AC)

Physical Characteristics

Overall Diameter	8.8 ± 0.2mm		
Bend Radius	Fixed 6 x OD,	Flexing	10 x OD
Temperature Rating	Fixed -20°C to 70°C,	Flexing	-10°C to 60°C
Weight	68 kg/km		

Transmission Performance

Frequency	1	4	10	16	20	31.25	62.5	100	155	200	300	350	MHz
Attenuation	2.1	3.90	6.2	7.90	8.9	11.2	16.2	21.0	26.6	30.7	38.7	41.4	dB
Return Loss	19.0	19.0	19.0	19.0	19.0	17.1	14.1	12.0	10.1	9.0	7.2	6.6	dB
NEXT	60.0	54.8	48.5	45.2	43.7	40.5	35.7	32.3	29.2	27.3	24.4	23.2	dB
PS NEXT	57.0	51.8	45.5	42.2	40.7	37.5	32.7	29.3	27.0	25.2	22.3	21.2	dB
ACRF	58.6	46.6	38.6	34.5	32.6	28.7	22.7	18.6	17.5	15.3	11.8	10.5	dB
PSACRF	55.6	43.6	35.6	31.5	29.6	25.7	19.7	15.6	11.8	9.6	6.1	4.7	dB

Standards

RoHS2 Compliance	Yes	UV Resistance	Good, ISO 4892-3†
CE Compliant	LVD (2014/35/EU)	Weather Resistance	Good, ISO 4892-3†
Manufactured in accordance to	TIA/EIA 568-C.2, ISO/IEC 11801		

*Suitable for installation where Band II 450/750v cables are present. Not suitable for connection to mains supply
 †500 hour test duration, equivalent to 9-12 months of northern Europe climate.

Tru Cables Tel: 01727 840 841 info@trucables.com www.trucables.com

Information and images on this datasheet are intended for guidance only and products may vary due to manufacturing changes, technical improvements and commercial factors. We reserve the right to amend the product information without notice or liability.

ISO 9001:2015 Certificate Number: DAS94272226/0/Q

Part Number: C5EFD
 Date: 30/10/2017
 Revision: 1.2
 Author: Checked:
 Page Number: 1 of 1