

Part No: C5THXX-E00
Description: The TruHD Cat 5E U/UTP cable has been tested and recommended by the HDBaseT Alliance making it the ideal choice for high speed data networks across a home or building.














TESTED TO
350MHz



Construction

Conductor : Bare Copper
 AWG : 24(1)
 Insulation Material : High Density Polyethylene (HDPE)
 Number of Pairs : 4
 Pair Identification : White/Blue, Blue/White; White/Orange, Orange/White
 : White/Green, Green/White; White/Brown, Brown/White
 Sheath Material : Low Smoke Halogen Free (LSHF)
 Sheath Colour : Replace XX on the end of the part number with the colour

00		04		08	
01		05		09	
02		06		10	
03		07			

Electrical Characteristics

Max. Conductor Resistance @ 20°C : ≤ 9.5 Ω/100m
 Max. Resistance Unbalanced : ≤ 2.5 %
 Nominal Impedance (1-100MHz) : 100 ± 15 Ω
 Mutual Capacitance : ≤ 5.6nF/100m
 Capacitance Unbalanced to Earth : ≤ 330 pF/ 100m
 NVP : 68.5 %
 Max. Delay Skew : ≤ 45 nS/ 100m
 Voltage Rating EN 50525-1 : 450/750V*
 Test Voltage : 2.5kV (AC)
 *Suitable for installation where Band II 450/750v cables are present. Not suitable for connection to mains supply

Physical Characteristics

Overall Diameter : 5.0 ± 0.2mm
 Bend Radius : Fixed 4 x OD Flexing 8 x OD
 Temperature Rating : Fixed -20°C to 60°C Flexing -10°C to 60°C
 Weight : 40 kg/km

Transmission Performance

Frequency	1	4	10	16	20	31.25	62.5	100	155	200	300	350	MHz
Attenuation	2.1	3.90	6.2	7.90	8.9	11.2	16.2	21.0	26.6	30.7	38.7	41.4	≤ dB
Return Loss	19.0	19.0	19.0	19.0	19.0	17.1	14.1	12.0	10.1	9.0	7.2	6.6	≥ dB
NEXT	60.0	54.8	48.5	45.2	43.7	40.5	35.7	32.3	29.2	27.3	24.4	23.2	≥ dB
PS NEXT	57.0	51.8	45.5	42.2	40.7	37.5	32.7	29.3	27.0	25.2	22.3	21.2	≥ dB
ACRF	58.6	46.6	38.6	34.5	32.6	28.7	22.7	18.6	17.5	15.3	11.8	10.5	≥ dB
PSACRF	55.6	43.6	35.6	31.5	29.6	25.7	19.7	15.6	11.8	9.6	6.1	4.7	≥ dB

Standards

Flame Retardant : BS EN 60332-1-2	Low Smoke Generation : BS EN 61034-2
Halogen Gas Emission : BS EN 60754-1&2	Approval : HDBaseT
RoHS3 Compliance : Yes	Manufactured in accordance to : TIA/EIA 568-C.2, ISO/IEC 11801
CE Compliant : LVD (2014/35/EU), CPR (305/2011)	CPR Classification : Eca (EN50575:2014+A1:2016)

FS Cables
Shoal Export

01727 840 841
+44 1727 849 841

sales@fscables.com
sales@shoal-export.com

www.fscables.com
www.shoal-export.com

Part Number: C5THXX-E00
 Date: 03/01/2020
 Revision: 1.3
 Author: GB Checked: GB
 Page Number: 1 of 1

Information and images on this technical datasheet are intended for guidance only and products may vary due to manufacturing changes, technical improvements and commercial factors. We reserve the right to amend the product information without notice or liability.