


**Part No:** C7HR08-B204  
**Description:** The TruLan Cat 7 S/FTP cable is the ideal choice for high speed data networks across a home, building or data centre.



### Construction

**Conductor** : Bare Copper  
**AWG** : 23(1)  
**Insulation Material** : Skin-Foam-Skin (SFS)  
**Number of Pairs** : 4  
**Pair Identification** : Blue/White, Orange/White,  
 : Green/White, Brown/White  
**Individual Screen** : Aluminium Foil, Each Pair (100% Coverage)  
**Drain Wire** : 0.40mm, Tinned Copper  
**Overall Screen** : Tinned Copper Wire Braid (30% Coverage)  
**Sheath Material** : Low Smoke Halogen Free (LSHF)  
**Sheath Colour** : Orange

### Electrical Characteristics

**Max. Conductor Resistance @ 20°C** : ≤ 9.5 Ω/100m  
**Max. Resistance Unbalanced** : ≤ 2.0 %  
**Nominal Impedance (1-100MHz)** : 100 ± 5 Ω  
**Mutual Capacitance** : ≤ 56 pF/km  
**Capacitance Unbalanced to Earth** : ≤ 1600 pF/km  
**NVP** : 77 % ± 3  
**Max. Delay Skew** : ≤ 25 nS/ 100m  
**Voltage Rating EN 50525-1** : 125V  
**Test Voltage** : 1kV

### Physical Characteristics

**Overall Diameter** : 7.5 ± 0.2mm  
**Bend Radius** : Fixed 4 x OD Flexing 8 x OD  
**Temperature Rating** : Fixed -20°C to 60°C Flexing -0°C to 50°C  
**Weight** : 70 kg/km

### Transmission Performance

Frequency	1	4	10	100	250	500	600	MHz
Attenuation	2.0	3.7	5.9	19.0	31.0	45.3	50.1	≤dB
Return Loss	34	30	27	20	17	15	15	≥dB
NEXT	75	66	60	45	39	35	34	≥dB
PS NEXT	72	63	57	42	36	32	31	≥dB
ACRF	68	56	48	28	20	14	12	≥dB
PS-ACRF	65	53	45	25	17	11	9	≥dB

### Standards

<b>Flame Retardant</b> : BS EN 60332-1-2	<b>Low Smoke Generation</b> : BS EN 61034-2
<b>Halogen Gas Emission</b> : BS EN 60754-1&2	<b>Manufactured in accordance to</b> : ISO/IEC 11801 Class F, EN 50288-4-1, ISO/IEC 61156-5
<b>RoHS3 Compliance</b> : Yes	<b>CPR Classification</b> : B2ca s1a, d1, a1 (EN50575:2014+A1:2016)
<b>CE Compliant</b> : LVD (2014/35/EU), CPR (305/2011)	