


**Description:** CW1308 Twisted Pair Telephone Cable PVC Black Sheath.



### Construction

Conductor Material : Plain Annealed Bare Copper  
 Conductor Stranding : 1/0.5mm  
 Insulation Material : Polyvinyl Chloride (PVC)  
 Number of Pairs : See table  
 Sheath Material : Polyvinyl Chloride (PVC)  
 Sheath Colour : Black  
 Core Identification : BT CW1308 (see table)

### Electrical Characteristics

Conductor Resistance @ 20°C : 97.8 Ω/km  
 Capacitance Unbalanced : 500 pF/500m  
 Insulation Resistance @ 20°C : > 50 MΩ/km

### Physical Characteristics

Overall Diameter : See table  
 Temperature Rating : 0°C to +60°C  
 Min. Bend Radius : 8 x OD  
 Weight : See table

### Standards

Flame Retardant : BS EN 60332-1-2  
 RoHS3 Compliant : Yes  
 CE Compliant : CPR (305/2011)  
 CPR Classification : Eca (EN 50575:2014+A1:2016)

Part No.	No. of Pairs	Weight (kg/km)	OD (mm)
3080300	3	28	5.0
3080400	4	34	5.8

### CW1308 Colour Code

Pair	A-Wire	B-Wire
1	White-Blue	Blue-White
2	White-Orange	Orange-White
3	White-Green	Green-White
4	White-Brown	Brown-White