



Easi-clip clip-on cable markers.

Key features.

- For cable diameters 0.85 - 19.0mm
- Markers are supplied pre-loaded on the applicator
- Suitable for areas such as underground installations, offshore chemical industry, food production and other demanding applications
- They provide an easy, cost-effective method of conveniently marking in situ on terminated cables from 0.1mm² to 0.5mm², using an integrated applicator

Available marks.

Black on white

A-Z 0-9 + - / . ± L1 L2 L3

Black on yellow

A-Z 0-9 + - / . ± L1 L2 L3

Colour coded



Specification.

Material:

Polyoxymethylene UL94 HB rated zero halogen material

Colour options:

Black on white, black on yellow, colour coded

Service temperature range:

-40°C to +125°C

Chemical resistance:

Oils, fuels and alkaline solutions



| Part number | Marker type | Cable dia. (mm) | For cable size (mm ²) | Applicator part number | Pack quantity |
|-------------|-------------|-----------------|-----------------------------------|------------------------|---------------|
| EC00* | STD00 | 0.85 - 1.1 | Fibre optic | - | 300 |
| EC01* | STD01 | 1.0 - 1.4 | 0.1 - 0.5 | - | 300 |
| EC02* | STD02 | 1.4 - 1.8 | 0.5 - 0.7 | - | 300 |
| EC03 | STD03 | 1.9 - 2.6 | 0.7 - 1.0 | - | 300 |
| EC05 | STD05 | 2.3 - 3.0 | 1.0 - 1.5 | - | 300 |
| EC06 | STD06 | 2.6 - 3.5 | 1.5 - 3.4 | - | 300 |
| EC09 | STD09 | 3.3 - 4.5 | 2.5 - 6.0 | - | 300 |
| EC012 | STD12 | 4.5 - 6.0 | 6.0 - 10.0 | - | 300 |
| EC015 | STD15 | 5.8 - 8.5 | 10.0 - 16.0 | EC015W | 50 |
| EC017 | STD17 | 8.5 - 11.5 | 16.0 - 25.0 | EC017W | 50 |
| EC021 | STD21 | 11.0 - 15.5 | 25.0 - 70.0 | EC021W | 50 |
| EC024 | STD24 | 15.0 - 19.0 | 70.0 - 95.0 | EC024W | 50 |

* Please note: L1, L2 and L3 are not available in EC00, EC01 and EC02