





WrappaSleeve: Standard Wrap Around Sleeving

WrappaSleeve is a self-extinguishing, lightweight wraparound sleeving for all shapes of cables and harnesses with a 150% capacity. It provides flexibility, spring back and high resistance to abrasion. It is designed to protect wiring, cables, pipes, hoses and foam insulation from mechanical degradation arising from exposure to touch conditions in vibrating installations. It can be installed by opening up the sleeve, feeding over the application and releasing.





| Part number | Colour | Bore size (mm) | Qty (m) |
|----------------|--------|----------------|---------|
| WRAP 5-HF | Black | 5.0 | 5 |
| WRAP 9-HF | Black | 9.0 | 5 |
| WRAP 13-HF | Black | 13.0 | 5 |
| WRAP 18-HF | Black | 18.0 | 5 |
| WRAP 25-HF | Black | 25.0 | 5 |
| WRAP 30-HF | Black | 30.0 | 5 |
| WRAP 35-HF | Black | 35.0 | 5 |
| WRAP 38-HF-5M | Black | 38.0 | 5 |
| WRAP 38-HF-25M | Black | 38.0 | 25 |

Specification.

<u>Material</u>

Woven Polyethylene Terephthalate

Colour options:

Black

<u>Service temperature range:</u> -50°C to +150°C

Melting Temperature: 250°C

Flammability:

UL224 VW-1 Self-Extinguishing

Chemical resistance:

Resistant to ammonium hydroxide, chlorine, diesel, detergents, ethanol, hydrochloric acid, inorganic solvents, mineral oils, white spirit and most chemicals and common fuels.

<u>Standards:</u> UL 224 Approved





