


Firetuf™ OFC-UT-NM Fire resistant Universal Central Tube Cable, variant in red

Indoor/Outdoor non-metallic LSHF-FR sheathed optical cable with 2 – 24 fibers. VDE: A/I-DQ(ZN)H



3rd party verification of the fire tests by BUREAU VERITAS December 2014

Application and installation

The application of this cable is circumstances where a very high degree of fire safety is required as the cable will function during a fire, has limited fire spread, has limited smoke generation and is halogen free.

The typical installation environment is indoor and indoor/outdoor in and between public buildings, in tunnels, metro lines and other places where one need very high degree of fire safety and support for critical communication.

This cable is also suitable shipboard application.

The primary means of installation is on cable ladders, raceways and cable trays. The cable may also be pulled into ducts. The cable can be installed outdoor in the open, but shall be not be installed directly exposed to the sun.

Standards

ISO 11801 2nd edition, EN 50173-1:2002, IEC 60794-1

Fire rating

Fire resistance tests

IEC 60331-25 (120) Fire resistance: 120 minutes at 750 °C (No fibre break)

EN 50200 PH 120 Fire resistance with fire and impact 120 minutes 830 °C (No fibre break)

EN 50200 ANNEX E PH 30 Fire resistance until 15 minutes of fire and impact alone , followed by 15 minutes of fire , impact and water spray at 830 °C (No fibre break)

BS 8434 - 2 Fire resistance until 60 minutes of fire and impact alone , followed by 60 minutes of fire , impact and water spray at 930 °C (No fibre break)

Flame retardant tests

IEC 60332-1-2 Single vertical wire test

Flame propagation test

IEC 60332-3-24 = Vertically-mounted bunched wires and cables

IEC 332-3C

Halogen acid & gas tests

IEC 60754-1 No halogens

IEC 60754-2 No acid matters

Smoke emission tests

IEC 61034-2 No dense smoke

Firetuf™ OFC-UT-NM Fire resistant Universal Central Tube Cable, variant in red

Construction

Loose tube	Ø4.0 mm jelly filled loose tube green colored with up to 2 - 24 fibres		
Fibre colour code	1	Red	13 Yellow w/mark per 100 mm
	2	Green	14 White w/mark per 100 mm
	3	Blue	15 Grey w/mark per 100 mm
	4	Yellow	16 Turquoise w/mark per 100 mm
	5	White	17 Orange w/mark per 100 mm
	6	Grey	18 Pink w/mark per 100 mm
	7	Brown	19 Yellow w/mark every 50 mm
	8	Violet	20 White w/mark every 50 mm
	9	Turquoise	21 Grey w/mark every 50 mm
	10	Black	22 Turquoise w/mark every 50 mm
	11	Orange	23 Orange w/mark every 50 mm
	12	Pink	24 Pink w/mark every 50 mm
Fire barrier	Tape(s)		
Strength member	Water blocked E-Glass fibre elements		
Ripcord	1		
Sheath	2.5 mm red LSHF-FR sheath according to EN 50290-2-27, UV stabilised		
Print legend	Draka Firetuf OFC-UT-NM CI-LSHF I/O <fibre count> <fibre type> <fibre brand> <item number> 05 <batch number> ISO11801 EN50173-1 IEC60794-1 IEC61034-2 IEC60754-1+2 IEC60332-3-24 EN50200e PH30 EN50200 PH120 BS8434-2 IEC60331-25 <Transmission class> Prysmian Group		

Physical properties

IEC 60794-1

Property	Test method	Value
Nominal outer diameter	-	12.1 mm
Nominal weight	-	167 kg/km
Maximum installation tensile strength	E1	2000 N ($\Delta l/l$ fibre $\leq 0.5\%$, $\Delta\alpha$ reversible) *
Compressive strength (crush)	E3	1500 N / 100 mm, max 5 min ($\Delta\alpha$ reversible) *
Impact	E7	No fibre break; 5 Nm, 3 impacts, r=300mm,
Torsion	E7	5 cycles ± 1 turn
Kink	E10	The cables do not form a kink when a loop is drawn together to a diameter of 20xD (Cable diameter) mm
Min. bending radius, unloaded	E11	R = 121 mm
Min. bending radius, loaded	-	R = 240 mm
Temperature range	F1	Storage: -30°C to +60°C Installation: 0°C to +50°C Operation: -25°C to +70°C. ($\Delta\alpha$ 0.05 dB /km)**
Water penetration	F5B	No water leakage after 24 hour, sample=3m, water=1m,

* Values for single-mode fibres, all optical measurements performed at 1550 nm,

** Values for multi-mode fibres, all optical measurements performed at 850 nm or 1300 nm with 0.10 dB as threshold (tensile and crush will not be performed for MM fibres)

Firetuf™ OFC-UT-NM Fire resistant Universal Central Tube Cable, variant in red

Prysmian group material code	Prysmian Group material description	Fibre count	Fibre type	Fibre data sheet
	OFC UT NM 08 OM1 C02-1	8	MM fiber 62.2/125 OM1	C02
	OFC UT NM 12 OM3 C31-1	12	MaxCap-BB-OM3	C31
	OFC UT NM 12 OS2 C03-1	12	ESMF single mode G.652.D	C03

Delivery form: Wooden drum with protection.
Standard delivery length: 4 km with a tolerance of +- 5%.

© PRYSMIAN GROUP 2015, All Rights Reserved

All sizes and values without tolerances are reference values. Specifications are for product as supplied by Prysmian Group: any modification or alteration afterwards of product may give different result.

The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Prysmian Group. The information is believed to be correct at the time of issue. Prysmian Group reserves the right to amend this specification without prior notice. This specification is not contractually valid unless specifically authorised by Prysmian Group.

C31: MaxCap-BB-OM3 Multimode Fibre

Specifications of cabled bend-insensitive OM3 fibre

General and Application

Prysmian MaxCap BendBright® OM3, laser-optimised, bend-insensitive, graded-index multimode fibres are designed for transmission speeds of 10 Gb/s and beyond. It is suitable for systems operating at 850 nm and 1300 nm wavelengths. MaxCap BendBright® OM3 fibres incorporate BendBright® technology to deliver enhanced macro-bending performance. Prysmian multimode fibres are produced with proprietary Plasma Chemical Vapour Deposition (PCVD) process.

Standards

IEC 60793-2-10: type A1a.2	ISO/IEC 11801 category OM3
TIA/EIA-492 AAAC	ANSI/TIA/EIA-568.C
ITU G.651.1	ISO/IEC 24764

Cabled Fibre Attenuation

Attribute	Measurement method	Units	Limits
Attenuation at 850 nm	IEC 60793-1-40	dB/km	≤ 3.0
Attenuation at 1300 nm	IEC 60793-1-40	dB/km	≤ 1.0

Optical Specifications (Bare Fibre)

Attribute	Measurement method	Units	Limits
Attenuation at 850 nm	IEC 60793-1-40	dB/km	≤ 2.5
Attenuation at 1300 nm	IEC 60793-1-40	dB/km	≤ 0.7
Attenuation Difference btw. 1380 nm and 1300 nm	IEC 60793-1-40	dB/km	≤ 3.0
Point Discontinuity at 850 nm and 1300 nm	IEC 60793-1-40	dB	≤ 0.1
Numerical Aperture	IEC 60793-1-43	-	0.200 ± 0.015

Bending Loss

Mandrel Radius =7.5 mm, 2 turns at 850/1300 nm	IEC 60793-1-40	dB	≤ 0.2 / ≤ 0.5
Mandrel Radius =15 mm, 2 turns at 850/1300 nm	IEC 60793-1-40	dB	≤ 0.1 / ≤ 0.3

Bandwidth

Overfilled Launch Modal Bandwidth (OFL) at 850 nm	IEC 60793-1-41	MHz • km	≥ 1500
Overfilled Launch Modal Bandwidth (OFL) at 1300 nm	IEC 60793-1-41	MHz • km	≥ 500
Effective Modal Bandwidth (EMB) at 850 nm	IEC 60793-1-49	MHz • km	≥ 2000

Multimode System Reach

Transmission Distance*	1000BASE-SX	1000 m
	10GBASE-SR	300 m
	40GBASE-SR4	140 m
	100GBASE-SR10	140 m
	100GBASE-SR4	70 m

*Indicated link distances require total connector loss ≤ 1.0 dB, and VCSEL spectral bandwidth of ≤ 0.45 nm

C31: MaxCap-BB-OM3 Multimode Fibre

Geometrical Specifications

Attribute	Measurement method	Units	Limits
Core diameter	IEC 60793-1-20	µm	50 ± 2.5
Core non-circularity	IEC 60793-1-20	%	≤ 5
Core-cladding concentricity error	IEC 60793-1-20	µm	≤ 1
Cladding diameter	IEC 60793-1-20	µm	125.0 ± 1.0
Cladding non-circularity	IEC 60793-1-20	%	≤ 0.7
Coating diameter - uncoloured	IEC 60793-1-21	µm	242 ± 7
Coating diameter - coloured	IEC 60793-1-21	µm	250 ± 15
Coating non-circularity	IEC 60793-1-21	%	≤ 5
Coating-cladding concentricity error	IEC 60793-1-21	µm	≤ 10

Mechanical Specifications

Attribute	Measurement method	Units	Limits
Proof stress level	IEC 60793-1-30	GPa	≥ 0.7 (1%)
Average strip force	IEC 60793-1-32	N	≥ 1.0 ≤ 3.0
Peak strip force	IEC 60793-1-32	N	≥ 1.3 ≤ 8.9

Group Index of Refraction

Attribute	Measurement method	Units	Limits
Typical Group index of refraction at 850 nm	IEC 60793-1-22	-	1.482
Typical Group index of refraction at 1300 nm	IEC 60793-1-22	-	1.477

© PRYSMIAN GROUP 2016, All Rights Reserved

All sizes and values without tolerances are reference values. Specifications are for product as supplied by Prysmian Group: any modification or alteration afterwards of product may give different result.

The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Prysmian Group. The information is believed to be correct at the time of issue. Prysmian Group reserves the right to amend this specification without prior notice. This specification is not contractually valid unless specifically authorised by Prysmian Group.