

Two Bolt Type Cleat(TB-Range)



Two (2) Bolt Plastic Type Cleat:

In all cable installations, an essential factor is to ensure that all cables are secured with the correct cleats for the cable, application, and environment. The TB series of cleats support and secure all cables in a single formation throughout the system during normal operation and during fault conditions that may occur. System integrity is maintained, and cable damage can be prevented.

The TB range of cleats comply with latest requirements to EN 61914:2016 & IEC 61914:2015 standards. They are manufactured from high density polypropylene with excellent resistant to ultraviolet light and adverse weather conditions. The cleats are designed to hold and retain all types of cables in a single formation.

The TB range of cable cleats are marked “BICC COMPONENTS - TBXX” along with the cable diameter range (XX-XX) accommodation covering diameters from 50mm to 94mm.

The short circuit ratings mentioned below are based on single core cable formation as per EN 61914:2016 & IEC 61914:2015 standards. Short circuit report for multicore cables is available upon request.

Test Standard: EN 61914:2016 & IEC 61914:2015					
Description:	Clause:	Classification:	Description:	Clause:	Classification:
Type	6.1.2	Non-Metallic	Resistance to Short Circuit	6.4.4 – 1short circuit	20kA RMS / 50kA Peak
Operating Temperature	6.2	-20°C to +60°C		6.4.5 – 2short circuits	20kA RMS / 50kA Peak
Impact Resistance	6.3.4	Heavy	Ultraviolet Light	6.5.1.2	Resistant to Ultraviolet Light
Lateral Retention	6.4.2	8 KN	Corrosion	6.5.2	Not Applicable
Axial Retention	6.4.3	0.3 KN	Needle Flame	10.1	>120 secs
Cleat Spacing			As cleat spacing is dependent on system fault level and cable diameter then please enquire with the cleat manufacturer for correct maximum cleat spacing, for the system design.		

Two Bolt Type Cleat(TB-Range)

Features:

- Low & Medium Voltage Single or Multi core Type Cables in a Single Formation.
- Cable Diameter Range from 50mm to 94mm.
- **Material:** High Density Polypropylene – Black Colour
- Suitable for Use With all Standard Ladder and Tray Systems.
- Operating Temperatures -20°C to +60°C.

Selection Table:

Item Code	Cable Diameters (mm)		Cleat Dimensions (mm)				Hole Fixings
	Min.	Max.	C	A	B	E	
TB01	50	58	89	102	45	80	2 x M10
TB02	56	64	93	102	45	80	2 x M10
TB03	62	70	98	114	45	92	2 x M10
TB04	68	76	104	114	50	92	2 x M10
TB05	74	82	110	126	50	104	2 x M10
TB06	80	88	118	126	50	104	2 x M10
TB07	86	94	121	136	60	114	2 x M10

Disclaimer: The dimension provided are for guidance and given in good faith, however BICC Components reserve the right to change these without prior notification.

