

**Part No.:** TSS04004H-C04  
**Description:** TruSound four core 4mm<sup>2</sup> speaker cable Low Smoke Halogen Free (LSHF) throughout with oxygen free bare copper conductors.




### Construction

Conductor Material : 99.999% Oxygen Free Bare Copper  
 Conductor Size : 4mm<sup>2</sup> (Class 5)  
 Insulation Material : Low Smoke Halogen Free (LSHF)  
 Number of Cores : 4  
 Sheath Material : Low Smoke Halogen Free (LSHF)  
 Sheath Colour : Violet  
 Core Identification : Red, Blue, Black, White

### Electrical Characteristics

Nominal Conductor Resistance : < 6.2 Ω/km  
 Insulation Resistance : > 200 MΩ.M  
 Voltage Rating : 450/750V *Applies to CE marked FSC/Tru branded stock only*  
 Test Voltage : 2.5kV for 5 Minutes

### Physical Characteristics

Overall Diameter : 11.5 ± 0.3mm  
 Min. Bend Radius : 15 x OD  
 Temperature Rating : -20°C to +70°C  
 Weight : 265 kg/km

### Standards

Flame Retardant : BS EN 60332-1-2  
 Low Smoke Generation : BS EN 61034-2  
 Halogen Gas Emission : BS EN 60754-1&2  
 RoHS3 Compliant : Yes  
 CE Compliant : LVD (2014/35/EU), CPR (305/2011)  
 CPR Classification : Cca s1a, d1, a1 (EN50575:2014+A1:2016)