

Part No.: TSS144H-E00
Description: TruSound 14awg four core speaker cable Low Smoke Halogen Free (LSHF) throughout with oxygen free bare copper conductors.




Construction

Conductor Material : 99.999% Oxygen Free Bare Copper
 Number of Strands : 105/0.16mm
 Insulation Material : Low Smoke Halogen Free (LSHF)
 Number of Cores : 4
 Sheath Material : Low Smoke Halogen Free (LSHF)
 Sheath Colour : Violet
 Core Identification : Red, Black, White, Green

Electrical Characteristics

Nominal Conductor Resistance : < 8.5 Ω/km
 Insulation Resistance : > 200 MΩ.M
 Voltage Rating : 450/750V *Applies to CE marked FSC/Tru branded stock only*
 Test Voltage : 2.5kV for 5 Minutes

Physical Characteristics

Overall Diameter : 9.1 ± 0.3mm
 Min. Bend Radius : 15 x OD
 Temperature Rating : 0°C to +70°C
 Weight : 165 kg/km

Standards

Flame Retardant : BS EN 60332-1-2
 Low Smoke Generation : BS EN 61034-2
 Halogen Gas Emission : BS EN 60754-1&2
 RoHS Compliant : Yes
 CE Compliant : LVD (2014/35/EU), CPR (305/2011)
 CPR Classification : Eca (EN50575:2014+A1:2016)
 UV and Weather Resistant : ISO 4892-3*
 : *Applies to all Batches ST***** Onwards

