

Description: Tri-Rated Wiring Cable, PVC, Conforming to BS6231 / UL758 / CSA22.2



Construction

Conductor Material : Plain Annealed Copper, Class 5
 Insulation Material : Polyvinyl Chloride, (PVC)
 Insulation Colour : Replace XX on the end of the part number with the colour

00	Black	04	White	08	Orange	11	Light Blue
01	Blue	05	Grey	09	Yellow	21	Dark Blue
02	Brown	06	Violet	10	Green		
03	Red	07	Pink	99	Green/ Yellow		

Characteristics

Nominal Conductor Resistance : BS EN 60228
 Voltage Rating : 0.6/1kV

Physical Characteristics

Overall Diameter : See Table
 Min. Bend Radius : 5 x OD
 Temperature Rating : -15°C to +90°C (BS 6231)
 : -15°C to +105°C (UL, CSA)
 Weight : See Table

Standards

Flame Retardant : BS EN 60332-1-2
 Manufactured in accordance to : BS EN 50525-2-31
 RoHS3 Compliant : Yes
 CE Compliant : LVD (2014/35/EU), CPR (305/2011)
 CPR Classification : Eca (EN50575:2014+A1:2016)

Part No.	Size mm ²	Weight kg/km	OD mm
TRIO05XX100	0.5	10	2.5
TRIO07XX100	0.75	13	2.7
TRIO10XX100	1.0	15	2.8

Description: Tri-Rated Wiring Cable, PVC, Conforming to BS6231 / UL758 / CSA22.2

Electrical Characteristics

Cross Section (mm ²)	Diameter	Weight (kg/km)	Current (a) 2 Cond.	Current (a) 3 Cond.	Voltage Drop (V/A km)
0.5	2.5	10	12	10	99.5
0.75	2.7	13	13	15	66.6
1.0	2.8	15	18	16	12.7

Reference method for 90°C insulation cables according to IEC 60364-5-52 in open air at 30°C ambient temperature.